

## CYCLE COAT (PASTER) INSULATING/ FIRING



<b>TANK</b>	<b>ISOCRIL PRIMER</b> Transparent acrylic water hardener Primer to be used as base coat on old and new plasters before applying water paints or distempers. <b>Application:</b> brush <b>Dilution:</b> water ratio 1:4 <b>Indicative yield:</b> 20 sqm./Liter per coat	Code	Package Liter
		190114	12
		19015	5
		190175	1
<b>TANK</b>	<b>PIGMENTED ISOCRIL PRIMER</b> White Water-based coloured acrylic primer to be used as base coat class 0 (*) on old and new plasters before applying water paints or class 1 (*) distempers. <b>Application:</b> brush class 2 (*) <b>Dilution:</b> water 30% <b>Indicative yield:</b> 10 sqm./Liter per coat (*)SAIANI colour bunch	Code	Package Liter
		190214	14
		19025	5
		1902CL014	14
		1902CL05	5
		1902CL114	14
		1902CL15	5
		1902CL214	14
		1902CL25	5
		<b>TANK</b>	<b>MICROACRIL PRIMER</b> Acrylic fine micro emulsion water primer with high-penetration and consolidation, as regularizing for different absorption plasters, old paints and various patches. <b>Application:</b> brush <b>Dilution:</b> water in relation to the requirements <b>Indicative yield:</b> 20 sqm./Liter per coat
190314	12		
19035	5		
190375	1		
<b>TANK</b>	<b>ALPHALOXAN PRIMER</b> Acryl-siloxanic Primer for mineral surfaces to be treated with acrylic and acrylic-siloxanic finishes of strong penetration.	Code	Package Liter
		ALPHALOXANP15	15
		ALPHALOXANP5	5



### NITROFIX IVAS

Transparent

Very high penetration solvent acrylic primer. For outdoors.

**Application:** brush, short-haired white wool roller

**Dilution:** 10%- Nitro anti-fog dilution.

**Indicative yield:** 8-10 sqm./Liter

## CYCLE COAT (PASTER) SKIM COATS/SPECIAL MORTARS

Code	Package Liter
AR0019	25
AR0036	5
AR0035	1
AR0114	25
AR0115	5

### RASOKOL PLASTER

Grey powder adhesive plaster for bonding and skimming of thermal insulation panels.

For indoor and outdoor

Grams 0.8 mm.

**Application:** spatula, trowel, Sponge trowel

**Mixing ratio:** 22-24% kg/sqm.

**Indicative yield:** 2 kg/sqm per mm of thickness

Code	Package kg.
RASOKOL	25

### WHITE GROBKOL

Silicated mineral. For indoors and outdoors.

grams 1.5 mm.

**Application:** spatula, trowel, sponge trowel.

**mixing ratio:** 22-24% kg/sqm.

**Indicative yield:** 2 kg/sqm per mm of thickness

Code	Package kg.
GROBKOL	20

### TOWER-ST MORTAR

Support: concrete

Fibered and thixotropic Mortar from restoring, high thickness medium fast hardening with possible thick float finish

Mix with 15/20% of water

Code	Package kg.
TOWERST	25

	Code	Package kg.
<p><b>TOWER-IP PLASTER</b>  <b>Support:</b> concrete            Anti-Carbonation and medium fast setting mortar plaster with float civilian finish of medium thickness.            Mix with 20/25% of water</p>	TOWERIP	25

	Code	Package kg.
<p><b>TOWER-ER MORTAR</b>  <b>Support:</b> plaster            Thixotropic repair Mortar medium thick and anti-withdrawal hardening for layers of coating on concrete and plasters (with its bottom)</p>	TOWERER	25

## CYCLE COAT (PASTER) SKIM COATS/SPECIAL MORTARS

	Code	Package kg.
<p><b>TOWER-FT SKIM COAT</b>  <b>Support:</b> plaster            Medium fast, low elastic modulus and non-shrink Skim coat,with float civilian finish of medium thickness.            Mix with 20/25% of water</p>	TOWERFT	25

	Code	Package kg.
<p><b>TOWER-FO MORTAR</b>  <b>Support:</b> plaster and concrete            thixotropic rough coat Mortar medium – fast hardening on coating on plasters.            Mix with 15/18% of water</p>	TOWERFO	25

	Code	Package kg.

### TOWER-IL - SKIM COAT

Support: concrete-plaster-masonry-drywall.

Grey medium fast hardening Skim coat, non-shrink, float civilian finish construction thickness

TPWERIL	25
---------	----

---

### TOWER-ET STUCCO

Support: plaster and concrete.

Cement skim Stucco for indoor and outdoor up to great thickness.

Mix with 35/45% of water

Code	Package kg.
------	-------------

TOWERET	25
---------	----

## CYCLE COAT (PASTER) SKIM COATS/SPECIAL MORTARS

		Code	Package lt.
<b>TECNOQUARZ-FIN PLUS (*)</b> Fine quartz flour high cover Micro- and colored cover , opaque aspect, insensitive to support alkalinity, anti-algae and mold, k Series , water repellent, while maintaining breathability. Application: brush-roller-spray Dilution:: water up to 20% Indicative yield: 3-4 sqm./lt (two coats) (*) from K125 to 135, K137-139-140-141, from K143 to K147, k149-150, k249-250, K301-K303-K305-K306-K308, from K310 to K318, K328	White	2300K14	14
	Micro- and colored mazz.	2300K5	5
	overlaid colors (*)	2300KS14	14
		2300KS5	5

		Code	Package kg.
<b>EXTERIOR PLUS 120-150 COATING</b> Continuous plastic coating, a wide range of action against algae blackening, homogeneous, compact, flexible and particularly suitable as a finish for exterior coatings. Application: metal or plastic trowel. dilution: ready to use indicative Yield: (120) 2 kg/sqm. per coat (150) -3.2 3.0 kg/sqm. per coat. Max grain size: (120) 1.2 mm. /(150) 1.5 mm. (*) <b>SAIANI</b> colour bunch <b>IMPORTANT:</b> the protection relating to biocides is sacrificial type; its durability and effectiveness of resistance over time depends on exposure and loops of intervention chosen only and in relation to exposure and location of support.	White	230124	24
	class 0 (*)	2301CL024	24
	class 1 (*)	2301CL124	24
	class 2 (*)	2301CL224	24

		Code	Package kg.
<b>EXTERIOR SILOX PLUS 120-150 COATING</b> Shaved-acril-siloxanic resins effect coating with full and uniform final look, for interior and exterior supports. Application: metal and plastic trowel <b>Diluition:</b> 1% water <b>Indicative Yield:</b> (120) 2.2 kg/sqm. for coat/(150) -2.5-3.0 kg/ sqm. per coat. <b>Max grain size:</b> (120) 1.2 mm. /(150) 1.5 mm. (*) <b>SAIANI</b> colour bunch	White	230224	24
	class 0 (*)	2302CL024	24
	class 1 (*)	2302CL124	24
	class 2 (*)	2302CL224	24

**EXTERIOR SILK SPECIAL PLUS 120-150 COATING**

Shaved- potassium silicate minerals coating with full and uniform final look, for interior and exterior supports.

**Application:** metal and plastic trowel

**Dilution:** 1% water

**Indicative Yield:** (120) 2.0 - 2.4 kg/sqm. per coat/(150) -2,5-3,0 kg/ sqm. per coat.

**Max grain size:** (120) 1.2 mm. /(150) 1.5 mm.

(\*)SAIANI colour bunch

White

class 0 (\*)

class 1 (\*)

class 2 (\*)

Code	Package kg.
230324	24
2303CL024	24
2303CL124	24
2303CL224	24