

ELIMINA/DELETE GRAFFITI ECOLOGICAL PRODUCT.

It acts in a selective way without damaging the support. Ecological product , free of chlorinated solvents harmful to the environment . The product affects neither the consistency nor the surface appearance as it acts on the part to be cleaned only . Apply the product and leave for about 10 minutes with an increase even up to 12 hours on porous or important layers. If after this treatment it will remain halos or shadows , apply **ELIMINA ALONI** (DELETE HALOS) to smooth surfaces . We recommend applying PREVEN GRAFFITI to prevent and protect surfaces from new vandalisms.

Product's Yield: 5-8 sqm / liter of product.

conf.

Code	Package liter
1200075	0,75
12005	5
120010	10
120020	20

ELIMINA/DELETE ANTIGRAFFITI HALOS

Alkaline based cleaner designed to remove the persistent graffiti halos and vandalic sentences.

Suitable for use on natural stones and absorbent building products.

DO NOT APPLY ON METALS, DELICATE POLISHED AND / OR LEADED STONES and NOT RESISTANT ALKALIS SURFACES.

The product should be used after surface cleaning with DELETE GRAFFITI product, mainly on porous surfaces having deep and strong halos.

Apply the product by brush or synthetic fiber roller leaving it for 15-20 minutes; the cleaning action can be aided with the use of brushes or abrasive pads. In case of strong halos, repeat the process and only at the end of treatment rinse a lot with pressurized water to remove residual products. It is recommended to complete the work with a PREVEN GRAFFITI product treatment to protect the surface from new vandalisms.

Indicative spreading rate: 4-7 sqm / liter of product.

Warnings: test first the product on a small part of the surface to avoid possible unwanted effects.

conf.

Code	Package liter
1201075	0,75
12015	5
120110	10
120120	20

PROTECT GRAFFITI LINE

conf.

Wax-based mountain and fluoropolymers product for the protection of natural stones, absorbing building artifacts and historical or monumental Properties.

Its active ingredients prevent the paints' rooting on treated areas, making it quite easy to remove it. It is an environmentally friendly water product, breathable and oil repellent at high resistance. It protects against smog too. The product must be applied on absorbent clean and dry surfaces only; it is ready for use and can be applied by roller, by brush or even by pressure steamer. The correct application involves two coats "wet on wet"; in presence of particularly porous surfaces it is recommended to apply the product up to complete saturation of the area. The product must be applied on the surface to be protected evenly without lumps and stagnations.

The product becomes effective when it will be dry. To clean Graffiti simply use hot water Vaporella under pressure hot water (80° c. 20/40 BAR). After each cleaning, protective part is removed too, it is necessary to repeat the treatment to renew protection. Indicative Yield: 5-7 sqm/liter of product.

Warning: test first the product on a small surface portion to avoid possible unwanted effects.

Code	Package liter
1202075	0,75
12025	5
120210	10
120220	20

